


Ceco Distributor Technical Data

SIZE LIMITS - UL LABELED HONEYCOMB CORE FIRE DOOR FIRE EXIT HARDWARE


⑤



HOURLY RATING	FACE GAGE	UL10b		UBC 7-2	
		MAX WIDTH	MAX HEIGHT	MAX WIDTH	MAX HEIGHT
1/3, 3/4, 1-1/2	16, 18	4'-0"	9'-0"	4'-0"	9'-0"
	20	3'-4"	7'-2"	3'-4"	7'-2"
3	16, 18	4'-0"	9'-0"	4'-0"	9'-0"

SINGLE SWING DOORS


⑥



HOURLY RATING	FACE GAGE	UL10b		UBC 7-2	
		MAX WIDTH	MAX HEIGHT	MAX WIDTH	MAX HEIGHT
1/3, 3/4, 1-1/2	16, 18	(2) 4'-0"	9'-0"	(2) 4'-0"	9'-0"
	20	(2) 3'-4"	7'-2"	(2) 3'-4"	7'-2"
3	16, 18	(2) 4'-0"	9'-0"	(2) 4'-0"	9'-0"

PAIR OF DOORS WITH HOLLOW METAL OR HARDWARE MULLION


⑦



STRIKE TYPE	HOURLY RATING	FACE GAGE	UL10b		UBC 7-2		ASTRAGAL INFO
			MAX WIDTH	MAX HEIGHT	MAX WIDTH	MAX HEIGHT	
LS OR ES	1/3, 3/4, 1-1/2	16, 18	8'-0"	9'-0"	8'-0"	9'-0"	OPTIONAL
ES	3	16, 18	6'-0"	7'-2"	6'-0"	7'-2"	REQUIRED
LS	3	16, 18	8'-0"	8'-0"	8'-0"	8'-0"	REQUIRED

PAIR OF DOORS WITH 3 POINT LATCHING


⑧



HOURLY RATING	FACE GAGE	UL10b		UBC 7-2	
		MAX WIDTH	MAX HEIGHT	MAX WIDTH	MAX HEIGHT
1/3, 3/4, 1-1/2	16, 18	8'-0"	9'-0"	8'-0"	9'-0"

STD. SWING - NO ASTRAGAL PERMITTED

DBL. EGRESS - ASTRAGAL OPTIONAL



PAIR OF DOORS WITH 3 OR 4 POINT LATCHING

LEGEND:

M = MORTISE FEH
 R = RIM FEH
 LS = LATCH STRIKE
 FM/RM = FIXED OR REMOVABLE MULLION

FB/SB = FLUSH OR SURFACE BOLT
 VR = VERTICAL ROD FEH
 ES = ELECTRIC STRIKE
 OBS = OPEN BACK STRIKE

CAUTION:

SOME LATCHING DEVICES MAY NOT BE APPROVED FOR USE ON DOORS UP TO MAXIMUM SIZES LISTED.