



Ceco Distributor Technical Data

SIZE LIMITS - UL LABELED
HONEYCOMB CORE FIRE DOOR
W/ADAMS RITE "INSET" F.E.H.



HOURLY RATING	FACE GAGE	UL10b		UBC 7-2	
		MAX WIDTH	MAX HEIGHT	MAX WIDTH	MAX HEIGHT
1/3, 3/4, 1-1/2	16, 18	4'-0"	9'-0"	4'-0"	9'-0"
	20	3'-4"	7'-2"	3'-4"	7'-2"
3	16, 18	4'-0"	9'-0"	4'-0"	9'-0"

SINGLE SWING DOORS




HOURLY RATING	FACE GAGE	UL10b		UBC 7-2	
		MAX WIDTH	MAX HEIGHT	MAX WIDTH	MAX HEIGHT
1/3, 3/4, 1-1/2	16, 18	8'-0"	9'-0"	8'-0"	9'-0"


STD. SWING (SHOWN) - NO ASTRAGAL PERMITTED

DBL. EGRESS (NOT SHOWN) - ASTRAGAL OPTIONAL

(1) HEAT ACTIVATED SPRING LOADED FIRE BOLT ASSEMBLY IS REQUIRED




PAIR OF DOORS WITH 2 POINT LATCHING



STRIKE TYPE	HOURLY RATING	FACE GAGE	UL10b		UBC 7-2		ASTRAGAL INFO
			MAX WIDTH	MAX HEIGHT	MAX WIDTH	MAX HEIGHT	
LS OR ES	1/3, 3/4, 1-1/2	16, 18	8'-0"	9'-0"	8'-0"	9'-0"	OPTIONAL
ES	3	16, 18	6'-0"	7'-2"	6'-0"	7'-2"	REQUIRED
LS	3	16, 18	8'-0"	8'-0"	8'-0"	8'-0"	REQUIRED


PAIR OF DOORS WITH 3 POINT LATCHING



HOURLY RATING	FACE GAGE	UL10b		UBC 7-2	
		MAX WIDTH	MAX HEIGHT	MAX WIDTH	MAX HEIGHT
1/3, 3/4, 1-1/2	16, 18	8'-0"	9'-0"	8'-0"	9'-0"

STD. SWING - NO ASTRAGAL PERMITTED

DBL. EGRESS - ASTRAGAL OPTIONAL



PAIR OF DOORS WITH 4 POINT LATCHING

LEGEND

M = MORTISE F.E.H.
VR = VERTICAL ROD F.E.H.
TRO = TOP ROD ONLY
ES = ELECTRIC STRIKE
LS = LATCH STRIKE

UL10b = CONVENTIONAL FIRE TEST
UBC 7-2 = NEW POSITIVE PRESSURE FIRE TEST
IN UNIFORM BUILDING CODE