


## Ceco Distributor Technical Data

SIZE LIMITS - WH LABELED  
HONEYCOMB CORE FIRE DOOR  
W/ADAMS RITE "INSET" F.E.H.




①



HOURLY RATING	FACE GAGE	UL10b	
		MAX WIDTH	MAX HEIGHT
1/3, 3/4, 1-1/2	16, 18	4'-0"	9'-0"
	20	3'-4"	7'-2"
3	16, 18	4'-0"	9'-0"

### SINGLE SWING DOORS

②




HOURLY RATING	FACE GAGE	UL10b	
		MAX WIDTH	MAX HEIGHT
1/3, 3/4, 1-1/2	16, 18	8'-0"	9'-0"

STD. SWING (SHOWN) - NO ASTRAGAL PERMITTED


DBL. EGRESS (NOT SHOWN) - ASTRAGAL OPTIONAL

(1) HEAT ACTIVATED SPRING LOADED FIRE BOLT ASSEMBLY IS REQUIRED



### PAIR OF DOORS WITH 2 POINT LATCHING


③



STRIKE TYPE	HOURLY RATING	FACE GAGE	UL10b		ASTRAGAL INFO
			MAX WIDTH	MAX HEIGHT	
LS OR ES	1/3, 3/4, 1-1/2	16, 18	8'-0"	9'-0"	OPTIONAL
ES	3	16, 18	6'-0"	7'-2"	REQUIRED
LS	3	16, 18	8'-0"	8'-0"	REQUIRED

### PAIR OF DOORS WITH 3 POINT LATCHING


④



HOURLY RATING	FACE GAGE	UL10b	
		MAX WIDTH	MAX HEIGHT
1/3, 3/4, 1-1/2	16, 18	8'-0"	9'-0"

STD. SWING - NO ASTRAGAL PERMITTED

DBL. EGRESS - ASTRAGAL OPTIONAL



### PAIR OF DOORS WITH 4 POINT LATCHING

**LEGEND**

- M = MORTISE F.E.H.
- VR = VERTICAL ROD F.E.H.
- TRO = TOP ROD ONLY
- ES = ELECTRIC STRIKE
- LS = LATCH STRIKE