


## Ceco Distributor Technical Data

### SIZE LIMITS - WH LABELED HONEYCOMB CORE FIRE DOOR SINGLE POINT LATCH


①



HOURLY RATING	FACE GAGE	MAX WIDTH	MAX HEIGHT
1/3, 3/4, 1-1/2	16, 18	4'-0"	9'-0"
	20	4'-0"	8'-0"
3	16, 18	4'-0"	9'-0"

#### SINGLE SWING DOORS


②



HOURLY RATING	FACE GAGE	MAX WIDTH	MAX HEIGHT	ASTRAGAL INFO
1/3, 3/4, 1-1/2	16, 18	8'-0"	9'-0"	OPTIONAL
	20	8'-0"	8'-0"	REQUIRED
3	16, 18	8'-0"	8'-0"	REQUIRED

#### PAIR OF DOORS


③



HOURLY RATING	FACE GAGE	MAX WIDTH	MAX HEIGHT	ASTRAGAL INFO
1/3, 3/4, 1-1/2	16, 18	8'-0"	9'-0"	OPTIONAL
	20	6'-0"	7'-2"	REQUIRED
3	16, 18	6'-0"	7'-2"	REQUIRED

#### PAIR OF DOORS WITH ELECTRIC STRIKE

④



HOURLY RATING	FACE GAGE	MAX WIDTH	MAX HEIGHT
1/3, 3/4, 1-1/2	16, 18	(2) 4'-0"	9'-0"
	20	(2) 4'-0"	8'-0"
3	16, 18	(2) 4'-0"	9'-0"

#### PAIR OF DOORS WITH HOLLOW METAL MULLION

**LEGEND:**

L = LATCH, SINGLE POINT  
 LS = LATCH STRIKE  
 FB/SB = FLUSH BOLT or SURFACE BOLT

ES = ELECTRIC STRIKE  
 FM/RM = FIXED or REMOVABLE MULLION

**CAUTION:**

SOME LATCHING DEVICES MAY NOT BE APPROVED FOR USE ON DOORS UP TO MAXIMUM SIZES LISTED.