



Ceco Distributor Technical Data

SIZE LIMITS - WH LABELED HONEYCOMB CORE FIRE DOOR FIRE EXIT HARDWARE




HOURLY RATING	FACE GAGE	MAX WIDTH	MAX HEIGHT
1/3, 3/4, 1-1/2	16, 18	4'-0"	9'-0"
	20	4'-0"	8'-0"
3	16, 18	4'-0"	9'-0"

SINGLE SWING DOORS




HOURLY RATING	FACE GAGE	MAX WIDTH	MAX HEIGHT
1/3, 3/4, 1-1/2	16, 18	(2) 4'-0"	9'-0"
	20	(2) 4'-0"	8'-0"
3	16, 18	(2) 4'-0"	9'-0"

PAIR OF DOORS WITH HOLLOW METAL OR HARDWARE MULLION




STRIKE TYPE	HOURLY RATING	FACE GAGE	MAX WIDTH	MAX HEIGHT	ASTRAGAL INFO
LS OR ES	1/3, 3/4, 1-1/2	16, 18	8'-0"	9'-0"	OPTIONAL
LS		20	8'-0"	8'-0"	OPTIONAL
ES	3	16, 18	6'-0"	7'-2"	REQUIRED
LS	3	16, 18	8'-0"	8'-0"	REQUIRED

PAIR OF DOORS WITH 3 POINT LATCHING



HOURLY RATING	FACE GAGE	MAX WIDTH	MAX HEIGHT	ASTRAGAL INFO
1/3, 3/4, 1-1/2	16, 18	8'-0"	9'-0"	OPTIONAL

PAIR OF DOORS WITH OPEN BACK STRIKE



SWING TYPE	HOURLY RATING	FACE GAGE	MAX WIDTH	MAX HEIGHT	ASTRAGAL INFO
STANDARD	1/3, 3/4, 1-1/2	16, 18	8'-0"	9'-0"	NOT ALLOWED
DBL. EGRESS			8'-0"	9'-0"	OPTIONAL
DBL. EGRESS	3		8'-0"	7'-2"	REQUIRED
STANDARD	1/3, 3/4, 1-1/2	20	8'-0"	8'-0"	NOT ALLOWED

PAIR OF DOORS WITH 4 POINT LATCHING

LEGEND:

M = MORTISE FEH
 R = RIM FEH
 LS = LATCH STRIKE
 FM/RM = FIXED or REMOVABLE MULLION

FB/SB = FLUSH or SURFACE BOLT
 VR = VERTICAL ROD FEH
 ES = ELECTRIC STRIKE
 OBS = OPEN BACK STRIKE

CAUTION:

SOME LATCHING DEVICES MAY NOT BE APPROVED FOR USE ON DOORS UP TO MAXIMUM SIZES LISTED.