


Ceco Distributor Technical Data

SIZE LIMITS – UL LABELED STEEL STIFFENED FIRE DOOR SINGLE POINT LATCH


①



HOURLY RATING	FACE GAGE	UL10b		UBC 7-2	
		MAX WIDTH	MAX HEIGHT	MAX WIDTH	MAX HEIGHT
1/3, 3/4, 1, 1-1/2	14	4'-0"	9'-0"	4'-0"	9'-0"
	16, 18	4'-0"	10'-0"	4'-0"	10'-0"
3	14	4'-0"	9'-0"	4'-0"	9'-0"
	16, 18	4'-0"	10'-0"	4'-0"	10'-0"

SINGLE SWING DOORS


②



HOURLY RATING	FACE GAGE	UL10b		UBC 7-2		ASTRAGAL INFO
		MAX WIDTH	MAX HEIGHT	MAX WIDTH	MAX HEIGHT	
1/3, 3/4, 1, 1-1/2	16, 18	8'-0"	8'-0"	8'-0"	8'-0"	OPTIONAL
	16, 18	8'-0"	10'-0"	8'-0"	10'-0"	REQUIRED
	14	8'-0"	9'-0"	8'-0"	9'-0"	REQUIRED
3	16, 18	8'-0"	10'-0"	8'-0"	10'-0"	REQUIRED
	14	8'-0"	9'-0"	8'-0"	9'-0"	REQUIRED

PAIR OF DOORS


③



HOURLY RATING	FACE GAGE	UL10b		UBC 7-2		ASTRAGAL INFO
		MAX WIDTH	MAX HEIGHT	MAX WIDTH	MAX HEIGHT	
1/3, 3/4, 1, 1-1/2	16, 18	8'-0"	9'-0"	8'-0"	9'-0"	OPTIONAL
3	16, 18	6'-0"	7'-2"	6'-0"	7'-2"	REQUIRED

PAIR OF DOORS WITH ELECTRIC STRIKE

④



HOURLY RATING	FACE GAGE	UL10b		UBC 7-2	
		MAX WIDTH	MAX HEIGHT	MAX WIDTH	MAX HEIGHT
1/3, 3/4, 1, 1-1/2	14	(2) 4'-0"	9'-0"	(2) 4'-0"	9'-0"
	16, 18	(2) 4'-0"	10'-0"	(2) 4'-0"	10'-0"
3	14	(2) 4'-0"	9'-0"	(2) 4'-0"	9'-0"
	16, 18	(2) 4'-0"	10'-0"	(2) 4'-0"	10'-0"

PAIR OF DOORS WITH HOLLOW METAL MULLION

LEGEND:

L = LATCH, SINGLE POINT
 LS = LATCH STRIKE
 FB/SB = FLUSH BOLT or SURFACE BOLT

ES = ELECTRIC STRIKE
 FM/RM = FIXED or REMOVABLE MULLION

CAUTION:

SOME LATCHING DEVICES MAY NOT BE APPROVED FOR USE ON DOORS UP TO MAXIMUM SIZES LISTED.