



## Ceco Distributor Technical Data

### SIZE LIMITS - UL LABELED STEEL STIFFENED FIRE DOOR FIRE EXIT HARDWARE




HOURLY RATING	FACE GAGE	UL10b		UBC 7-2	
		MAX WIDTH	MAX HEIGHT	MAX WIDTH	MAX HEIGHT
1/3, 3/4, 1, 1-1/2	14	4'-0"	9'-0"	4'-0"	9'-0"
	16, 18	4'-0"	10'-0"	4'-0"	10'-0"
3	14	4'-0"	9'-0"	4'-0"	9'-0"
	16, 18	4'-0"	10'-0"	4'-0"	10'-0"

SINGLE SWING DOORS




HOURLY RATING	FACE GAGE	UL10b		UBC 7-2	
		MAX WIDTH	MAX HEIGHT	MAX WIDTH	MAX HEIGHT
1/3, 3/4, 1, 1-1/2	14	(2) 4'-0"	9'-0"	(2) 4'-0"	9'-0"
	16, 18	(2) 4'-0"	10'-0"	(2) 4'-0"	10'-0"
3	14	(2) 4'-0"	9'-0"	(2) 4'-0"	9'-0"
	16, 18	(2) 4'-0"	10'-0"	(2) 4'-0"	10'-0"

PAIR OF DOORS WITH HOLLOW METAL OR HARDWARE MULLION




HOURLY RATING	STRIKE TYPE	FACE GAGE	UL10b		UBC 7-2		ASTRAGAL INFO
			MAX WIDTH	MAX HEIGHT	MAX WIDTH	MAX HEIGHT	
1/3, 3/4, 1, 1-1/2	LS	16, 18	8'-0"	8'-0"	8'-0"	8'-0"	OPTIONAL
		16, 18	8'-0"	10'-0"	8'-0"	10'-0"	REQUIRED
	ES	14	8'-0"	9'-0"	8'-0"	9'-0"	REQUIRED
		16, 18	8'-0"	9'-0"	8'-0"	9'-0"	OPTIONAL
3	LS	16, 18	8'-0"	10'-0"	8'-0"	10'-0"	REQUIRED
		14	8'-0"	9'-0"	8'-0"	9'-0"	REQUIRED
	ES	16, 18	6'-0"	7'-2"	6'-0"	7'-2"	REQUIRED

PAIR OF DOORS WITH 3 POINT LATCHING



HOURLY RATING	FACE GAGE	UL10b		UBC 7-2		ASTRAGAL INFO
		MAX WIDTH	MAX HEIGHT	MAX WIDTH	MAX HEIGHT	
1/3, 3/4, 1, 1-1/2	16, 18	8'-0"	8'-0"	8'-0"	8'-0"	OPTIONAL

PAIR OF DOORS WITH OPEN BACK STRIKE



SWING TYPE	HOURLY RATING	FACE GAGE	UL10b		UBC 7-2		ASTRAGAL INFO
			MAX WIDTH	MAX HEIGHT	MAX WIDTH	MAX HEIGHT	
STANDARD	1/3, 3/4, 1, 1-1/2	16, 18	8'-0"	9'-0"	8'-0"	8'-0"	NOT ALLOWED
DBL. EGRESS			8'-0"	8'-0"	8'-0"	8'-0"	OPTIONAL
DBL. EGRESS			8'-0"	10'-0"	8'-0"	10'-0"	REQUIRED
DBL. EGRESS			8'-0"	10'-0"	8'-0"	10'-0"	REQUIRED

PAIR OF DOORS WITH 4 POINT LATCHING

**LEGEND:**

M = MORTISE FEH  
 R = RIM FEH  
 LS = LATCH STRIKE  
 FM/RM = FIXED or REMOVABLE MULLION

FB/SB = FLUSH or SURFACE BOLT  
 VR = VERTICAL ROD FEH  
 ES = ELECTRIC STRIKE  
 OBS = OPEN BACK STRIKE

**CAUTION:**

SOME LATCHING DEVICES MAY NOT BE APPROVED FOR USE ON DOORS UP TO MAXIMUM SIZES LISTED.

