



## Ceco Distributor Technical Data

### SIZE LIMITS - WH LABELED STEEL STIFFENED FIRE DOOR FIRE EXIT HARDWARE




HOURLY RATING	FACE GAGE	MAX WIDTH	MAX HEIGHT
1/3, 3/4, 1, 1-1/2	14	4'-0"	9'-0"
	16, 18	4'-0"	9'-0"
3	14	4'-0"	9'-0"
	16, 18	4'-0"	9'-0"

SINGLE SWING DOORS



HOURLY RATING	FACE GAGE	MAX WIDTH	MAX HEIGHT
1/3, 3/4, 1, 1-1/2	14	(2) 4'-0"	9'-0"
	16, 18	(2) 4'-0"	9'-0"
3	14	(2) 4'-0"	9'-0"
	16, 18	(2) 4'-0"	9'-0"


PAIR OF DOORS WITH HOLLOW METAL OR HARDWARE MULLION



HOURLY RATING	STRIKE TYPE	FACE GAGE	MAX WIDTH	MAX HEIGHT	ASTRAGAL INFO
1/3, 3/4, 1, 1-1/2	LS or ES	16, 18	8'-0"	9'-0"	OPTIONAL
	LS	14	8'-0"	9'-0"	REQUIRED
3	LS	16, 18	8'-0"	9'-0"	OPTIONAL*
	LS	14	8'-0"	9'-0"	REQUIRED
	ES	16, 18	6'-0"	7'-2"	OPTIONAL*


PAIR OF DOORS WITH 3 POINT LATCHING

\*NFPA-80 AND MANY BUILDING CODES REQUIRE THE USE OF AN OVERLAPPING ASTRAGAL ON 3 HR. RATED PAIRS. CHECK WITH AUTHORITY HAVING JURISDICTION PRIOR TO INSTALLATION OF A 3 HR. PAIR W/O AN ASTRAGAL.



HOURLY RATING	FACE GAGE	MAX WIDTH	MAX HEIGHT	ASTRAGAL INFO
1/3, 3/4, 1, 1-1/2	16, 18	8'-0"	8'-0"	OPTIONAL
1/3, 3/4, 1, 1-1/2	14	8'-0"	8'-0"	REQUIRED

PAIR OF DOORS WITH OPEN BACK STRIKE



SWING TYPE	HOURLY RATING	FACE GAGE	MAX WIDTH	MAX HEIGHT	ASTRAGAL INFO
STANDARD	1/3, 3/4, 1, 1-1/2	16, 18	8'-0"	9'-0"	NOT ALLOWED
DBL. EGRESS			8'-0"	9'-0"	OPTIONAL
STANDARD	3	16, 18	8'-0"	9'-0"	NOT ALLOWED*
DBL. EGRESS			8'-0"	9'-0"	OPTIONAL*

PAIR OF DOORS WITH 4 POINT LATCHING

**LEGEND:**

M = MORTISE FEH  
R = RIM FEH  
LS = LATCH STRIKE  
FM/RM = FIXED or REMOVABLE MULLION

FB/SB = FLUSH or SURFACE BOLT  
VR = VERTICAL ROD FEH  
ES = ELECTRIC STRIKE  
OBS = OPEN BACK STRIKE

**CAUTION:**

SOME LATCHING DEVICES MAY NOT BE APPROVED FOR USE ON DOORS UP TO MAXIMUM SIZES LISTED.

