


Ceco Technical Architectural Data

SIZE LIMITS - WH LABELED SOLID CORE FIRE DOOR SINGLE POINT LATCH


①



HOURLY RATING	FACE GAGE	MAX WIDTH	MAX HEIGHT
1/3, 3/4, 1-1/2, 3	20	4'-0"	8'-0"
	16, 18	4'-0"	9'-0"

SINGLE SWING DOORS


②



HOURLY RATING	FACE GAGE	MAX WIDTH	MAX HEIGHT	ASTRAGAL INFO
1/3, 3/4	20	8'-0"	8'-0"	REQUIRED
	16, 18	8'-0"	9'-0"	REQUIRED
1-1/2	20	8'-0"	8'-0"	REQUIRED
	16, 18	8'-0"	9'-0"	REQUIRED
3	20	7'-4"	7'-2"	REQUIRED
	16, 18	7'-4"	9'-0"	REQUIRED

PAIR OF DOORS

③



HOURLY RATING	FACE GAGE	MAX WIDTH	MAX HEIGHT
1/3, 3/4, 1-1/2, 3	20	(2) 4'-0"	8'-0"
	16, 18	(2) 4'-0"	9'-0"

PAIR OF DOORS WITH HOLLOW METAL MULLION

LEGEND:

L = LATCH, SINGLE POINT
 LS = LATCH STRIKE
 FB/SB = FLUSH BOLT or SURFACE BOLT

FM/RM = FIXED or REMOVABLE MULLION

1/3 HOUR INCLUDES BOTH WITH & WITHOUT HOSE STREAM.

