


Ceco Distributor Technical Data

SIZE LIMITS - WH LABELED SOLID CORE FIRE DOOR FIRE EXIT HARDWARE


④



HOURLY RATING	FACE GAGE	MAX WIDTH	MAX HEIGHT
1/3, 3/4, 1-1/2, 3	20	4'-0"	8'-0"
	16, 18	4'-0"	9'-0"

SINGLE SWING DOORS


⑤



HOURLY RATING	FACE GAGE	MAX WIDTH	MAX HEIGHT
1/3, 3/4, 1-1/2, 3	20	(2) 4'-0"	8'-0"
	16, 18	(2) 4'-0"	9'-0"

PAIR OF DOORS WITH HOLLOW METAL OR HARDWARE MULLION


⑥



HOURLY RATING	FACE GAGE	MAX WIDTH	MAX HEIGHT	ASTRAGAL INFO
1/3, 3/4, 1-1/2	20	8'-0"	8'-0"	REQUIRED
	16, 18	8'-0"	9'-0"	REQUIRED
3	20	7'-4"	7'-2"	REQUIRED
	16, 18	7'-4"	9'-0"	REQUIRED

PAIR OF DOORS WITH 3 POINT LATCHING

⑦



HOURLY RATING	FACE GAGE	MAX WIDTH	MAX HEIGHT	ASTRAGAL INFO
1/3, 3/4, 1-1/2,	16, 18	8'-0"	9'-0"	NOT ALLOWED
	20	8'-0"	8'-0"	NOT ALLOWED

PAIR OF DOORS WITH 4 POINT LATCHING

LEGEND:

- M = MORTISE FEH
- R = RIM FEH
- LS = LATCH STRIKE
- FM/RM = FIXED OR REMOVABLE MULLION

- FB/SB = FLUSH OR SURFACE BOLT
- VR = VERTICAL ROD FEH

1/3 HOUR INCLUDES BOTH WITH & WITHOUT HOSE STREAM

