


## Ceco Technical Architectural Data

### SIZE LIMITS – UL LABELED POLYURETHANE CORE FIRE DOOR SINGLE POINT LATCH


①



HOURLY WAGE	FACE GAGE	MAX WIDTH	MAX HEIGHT
1/3, 3/4, 1-1/2	14, 16, 18, 20	4'-0"	8'-0"
3	14, 16, 18	4'-0"	8'-0"

#### SINGLE SWING DOORS


②



HOURLY RATING	FACE GAGE	MAX WIDTH	MAX HEIGHT	ASTRAGAL INFO
1/3, 3/4, 1-1/2	16, 18, 20	8'-0"	8'-0"	OPTIONAL
3	16, 18	8'-0"	8'-0"	REQUIRED

#### PAIR OF DOORS

③



HOURLY RATING	FACE GAGE	MAX WIDTH	MAX HEIGHT
1/3, 3/4, 1-1/2	14, 16, 18, 20	(2) 4'-0"	8'-0"
3	14, 16, 18	(2) 4'-0"	8'-0"

#### PAIR OF DOORS WITH HOLLOW METAL MULLION

**LEGEND:**

L = LATCH, SINGLE POINT

LS = LATCH STRIKE

FB/SB = FLUSH BOLT or SURFACE BOLT

FM/RM = FIXED or REMOVABLE MULLION

