

04/11/18

Phone: 888.264.7474 Fax: 866.465.9975 Website:www.cecodoor.com

Dear Distribution Partner,

Ceco Door is proud to announce the expansion of our Attack Resistant Opening which enhances safety and security by delaying access to an attacker. Corbin Russwin and Yale mortise locks have been added to the Attack Resistant product line. Standard doors, frames, and hardware, along with special attack resistant glazing will suppress unauthorized entry until first responders can neutralize the threat to the classroom or any occupants in the building. This product can be used for interior or exterior applications and is perfect for new construction and retro-fit projects.

Hardware:

- **NEW** Corbin Russwin ML2000 Series mortise lock with deadbolt and VR escutcheon*
- **NEW** Yale SL8800 Series mortise lock with deadbolt and SL escutcheon*
- SARGENT 8200 Series mortise lock with dead bolt and LS escutcheon
- McKinney 3-4 each 4 ½" x 4 ½" standard weight hinges, Pemko steel continuous hinges optional
*equivalent hardware not tested

Sizes:

- 2'8" x 6'8" - 4'0" x 8'0" single door opening (outswing)

Door Types:

- Legion, Regent and Imperial series doors with 16 gauge face sheets

Frame Types:

- SU/SQ and BU/BQ series 16 gauge (14 gauge optional)
- 3 Piece knock down or welded
- Welded sidelights and borrowed lights

Glass and Glazing:

- School Guard Glass SG5™
- Narrow vision or half glass utilizing type 2 (Imperial) or 4881 flush kits (Regent and Legion) factory installed in the door
- Sidelight glass up to 47" x 92.75" visible and borrowed light up to 47" x 95" visible provided with frames and field installed by others. (See tech manual for more details)

Test Methods and Standards:

- 5-aa10 - Certification Standards for Reinforcing and Testing of Standard Wood and Hollow Metal Doors, Frames, Glass and Hardware – 30 shots (7.62 mm) fired at glass and 30 shots (7.62 mm) fired at door hardware in a 6"x 6" area. Door then remained closed after 4 minutes of attack by single assailant using hand tools of various types as allowed in test.
- ASTM C1036 - Standard Specification-Flat Glass
- ASTM C1172 - Standard Specification for Laminated Architectural Flat Glass
- ANSI Z97.1 - Safety Materials Used in Buildings
- UL 972 – Standard for Burglary Resisting Glazing Material

To order the Attack Resistant Door Opening write "ARG" for attack resistant in field 19 miscellaneous construction options on your Ceco Door order form. List pricing and technical data is available on the distributor resources page of the OrderPro site.

If you have any questions, please contact your Ceco Door Customer Service Professional or your local ASSA ABLOY Door Security Solutions Representative.

ASSA ABLOY, the global leader
in door opening solutions.