

# Sound-Tech Xpress System<sup>+</sup>

STC 56-66 Hollow Metal Door and Frame



Ceco Door is proud to announce the addition of an ultra high STC 56-66 hollow metal door and frame system to the Sound-Tech Xpress acoustical product line. This will serve as a complete solution for assemblies requiring sound resistance from STC 56-66. The new Sound-Tech Xpress<sup>+</sup> STC 56-66 system also received an OITC (outdoor/indoor transmission class) rating of 46. The assembly was 3rd party tested to ASTM E90, E1332 and E413.

## Typical Applications:

Auto Industry/High Power Machinery  
Sound Studios  
Medical Field (hearing impaired sound booth)  
Manufacturing test lab

Sound transmission loss third party tested.  
Tested to ASTM E90, E1332 and E413. Compliant with HMMA 865 and SDI 128 specifications.

Ceco Door  
9159 Telecom Drive • Milan, TN 38358  
Tel (888) 232-6366 • Fax (888) 232-6462  
archhelp@cecodoor.com • www.cecodoor.com

## Options

- STC 56-66 and OITC 46
- Up to 4'0" x 8'0" configurations
- Single swing, communicating door and frame system
- 11" minimum frame depth with standard 2" face and adjustable perimeter seals
- Cam lift hinges
- Flat saddle thresholds
- Flush doors
- Prepped for cylindrical locks
- Adjustable door bottoms

CEC-112-06/15