

4/11/18

Phone: 888.264.7474 Fax: 866.465.9975 Website: [www.cecodoor.com](http://www.cecodoor.com)

Dear Distribution Partner,

Ceco Door is pleased to announce expansions in the StormPro tornado resistant assembly product offering. These expansions include, new StormPro fire rated single shutter and StormPro communicating frame availability. Please see below information for more details.

### **StormPro Fire Rated Shutter**

- Single only
- Fire rated up to and including 3 hours in accordance with UL 10B, UL 10C, UL 1784 and NFPA 252
- Opening size 2'6" x 3'0" to 4'0" x 6'8"
- 4" thru 14" jamb depth welded 14 gauge A60 galvanized (CRS optional) 4-sided frame with 3-sided frame option and 4" face head option
- 14 gauge A60 galvanized (CRS optional) door construction
- Corbin Russwin FE6700 Series
- SARGENT FM6100 Series
- All current approved shutter assembly hardware is available for this product

### **StormPro Communicating Frame**

- Singles and pairs
- For use with StormPro Multi-Point lock assemblies including Corbin Russwin FE6600 or SARGENT FM7300 hardware and adjacent non-classified door
- Designed for non-classified doors to be used daily with StormPro doors held open in non-threatening conditions then StormPro doors can be closed with severe weather

All StormPro assemblies meet FEMA P320 (2014) and P361 (2015) guidelines and are third-party classified through Underwriters Laboratories to ICC 500 (2014). StormPro tornado resistant assemblies come with the certification label attached.

Please see the updated marketing materials available on [www.cecodoor.com](http://www.cecodoor.com) and on the distributor resources area of the OrderPro site.

If you have any questions, please contact your Ceco Door Customer Service Professional or your local ASSA ABLOY Door Security Solutions Representative.