

StormPro® Multi-Point Exit Tornado Resistant Assembly UL Classified to ICC500 - 2014



Ceco Door StormPro® Multi-Point Exit assemblies include paired openings 6'0" x 6'8" minimum through 8'0" x 8'0" maximum with a required mullion. Single openings are available from 3'0" x 6'8" minimum to 4'0" x 8'0" maximum. These StormPro® assemblies give end-users another option for creating highly functional safe rooms with easy means of egress.

The StormPro® Multi-Point Exit assembly helps shield occupants in a safe room from flying debris. The assemblies are UL classified to ICC-500 2014 and comply with FEMA P320 and P361. StormPro® doors are also fire rated up to and including 3 hours. As with all StormPro® products, the third party Underwriters Laboratory certification labels are applied to each assembly.

Ceco Door
9159 Telecom Drive • Milan, TN 38358
Tel (888) 232-6366 • Fax (888) 232-6462
archhelp@cecodoor.com
www.cecodoor.com

ASSA ABLOY, the global leader
in door opening solutions

Available Sizes:

- Pairs 6'0" x 6'8" minimum to 8'0" x 8'0" maximum
- Singles 3'0" x 6'8" minimum to 4'0" x 8'0" maximum

Frame Type:

- StormPro 14 gauge frame single, 4" depth thru 14"
StormPro 14 gauge frame pairs, 5-1/2" depth thru 14"
- 4" head option
- Masonry or EO anchors

Door Type:

- 16 gauge StormPro door with polystyrene core and liner
(Honeycomb core if fire rated)

Hardware Options:

- Multi-Point Exit Device:
Corbin Russwin FE5400S
- Hardware Mullion:
Corbin Russwin FE707A Series or
FE708A Series

Hinges:

- MCKINNEY SP BUTT HINGES
- MCKINNEY MCK-HG305,
MCK-HG305WT10 and MCK-FM300
Continuous hinges
- MARKAR HG305, HG305WT10,
FM300, FM300WT continuous hinges

Accessories:

- Door closers, perimeter seals, electronic power transfer, door position switches, holders/stops, viewers, rod guards and kick plates are also available