

StormPro® Window Shutter System UL Classified to ICC500 - 2014



Securing a Facility During a Tornado

Keeping windows secured during a tornado can be accomplished with the same proven technology that's been used for door openings for years. The Ceco Door StormPro® Window Shutter is designed for safe rooms that require natural lighting from windows during normal, non-threatening conditions. The Ceco Door StormPro® Window Shutter meets FEMA guidelines and ICC 500-2014 standards.

StormPro® Window Shutter Systems include a 4-sided StormPro frame unit with StormPro® door and hardware. The units are installed inside the room in front of conventional exterior windows. When a severe weather threat occurs, the StormPro® Window Shutter is closed creating a level of security equal to an approved storm shelter.

- **Shutter Construction** utilizes heavy duty door and hardware products to withstand the added forces on smaller units.
- **Multi-Point locking shutter hardware** specifically designed for the unique requirements of shutters including optional lever heights, along with enhanced structural design.
- **Window Option** which allows the unit to be multi-purpose serving as a shutter and exterior window within the same assembly. This eliminates the need for an additional exterior window and provides the building owner with reduced labor and material costs.

Ceco Door is your one convenient source for all door and window building envelope Windstorm certified products. Verify your anchor details at: www.cecodoor.com.

Ceco Door
9159 Telecom Drive • Milan, TN 38358
Tel (888) 232-6366 • Fax (888) 232-6462
archhelp@cecodoor.com • www.cecodoor.com

Ceco is a brand associated with AADG, Inc., an ASSA ABLOY Group company. Copyright © 2018, AADG, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of AADG, Inc. is prohibited.

StormPro® Window Shutter System Door, Frame, and Hardware Options

Size Limitations:

Single:

- Minimum 2'6" x 3'0"
- Maximum 4'0" x 6'8"

Pair:

- Minimum 5'0" x 4'0"
- Maximum 8'0" x 6'8"

Call factory for other sizes

Door:

- 14 gauge A60 galvanized polystyrene core with steel liner
- Optional Cold Rolled Available
- Optional UL fire rating up to and including 3 hour singles only

Frame:

- 14 gauge A60 galvanized four sided frame
- Optional three sided frames
- Optional Cold Rolled Available
- 4" thru 14" jamb depths
- 4" face head option
- Use with existing wall anchors or masonry anchors

Hardware:

(concealed multi-point locks/hinges)

- Corbin Russwin FE6700 Series
- SARGENT FM6100 Series
- McKINNEY Model MCK-HG305 continuous hinge
- McKINNEY Model MCK-HG305WT10 wide throw continuous hinge
- Markar Model HG305 wide throw continuous hinge
- Markar Model HG305WT10 wide throw continuous Hinge
- McKINNEY Model SP3786 butt hinges including wide throw options
- McKINNEY Model SP3386 butt hinges including wide throw options

Accessories:

- Door closers
- Perimeter seals
- Electronic power transfer and door
- Position switches
- Door holders
- Door viewer

(See tech pages for more details)

*Due to the nature of shutter applications the SARGENT and Corbin Russwin multipoint locks for shutters do not require factory installation.

The Ceco Door StormPro® window shutter system is third party certified through Underwriters Laboratories, and comes with UL certification labels attached to the door and frame.

ASSA ABLOY, the global leader
in door opening solutions

CEC-106-03/18